



## Square RetractaPost-GL 745 (Galvanised)



### The AUTOPA Square RetractaPost-GL 745

The Square RetractaPost-GL 745 offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically. The post is 745mm above ground when raised and is fabricated from square mild steel tube which is then galvanised.

When lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.

The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

*Shown is 90mm x 90mm version of the RetractaPost-GL with optional AUTOPA Red & White chevron reflective label.*

### Product Range

| Order Code   | Description                         | Lift-up Weight | Weight |
|--------------|-------------------------------------|----------------|--------|
| 138 130 381  | 60mm x 60mm (Galvanised)            | 5.4kg          | 18.4kg |
| 138 130 386  | 60mm x 60mm (Galvanised and Colour) | 5.6kg          | 18.6kg |
| 138 130 427  | 70mm x 70mm (Galvanised)            | 6.2kg          | 19.2kg |
| 138 130 427c | 70mm x 70mm (Galvanised and Colour) | 6.2kg          | 19.2kg |
| 138 130 421  | 90mm x 90mm (Galvanised)            | 10.8kg         | 41.5kg |
| 138 130 423  | 90mm x 90mm (Galvanised and Colour) | 11.1kg         | 41.8kg |

### Accessories & installation parts

|             |   |
|-------------|---|
| 138 811 290 | Spare key (please specify key number/product) |
| 138 810 598 | AUTOPA Red & White Chevron Reflective Label   |

### Product details

745mm Tall (When raised).

1070mm Below Ground.

Galvanised or galvanised and coated finish.

### Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.

An excavated hole of approximately 1,200mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete.

The lid of the post should be no more than 10mm above finished ground level.

Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar.

This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103