







The VELOPA Birmingham Cycle Stand

The VELOPA Birmingham Cycle Stand features an integrated signage plate and tapping rail, making it fully compliant with the cycle parking recommendations on the Birmingham transport network. The signage plate incorporates the Cycle Parking 'P' and cycle symbol signs as standard ensuring cycle parking areas are easily identifiable at all times.

The design of the Birmingham Cycle Stand allows cyclists to secure the frame and wheel of their bicycles to the stand using their own lock. Each stand is suitable for securing up to two bicycles.

Manufactured from galvanised steel tube and ragged as standard; flanged, colour coated and stainless steel versions are also available. RAL/BS numbers must be specified at time of order. Reflective tape can be added to the stand to further enhance visibility if required.

Product Range

Order Code	Description	Weight
138 515 270	Ragged (Galvanised)	15.2kg
138 515 275	Flanged (Galvanised)	13.8kg
138 515 272	Ragged (Galvanised and Colour)	15.2kg
138 515 277	Flanged (Galvanised and Colour)	13.8kg
138 515 274	Ragged (Stainless)	12.0kg
138 515 279	Flanged (Stainless)	11.2kg

Installation Parts

138 100 994 M12 Expanding Bolt (6 required per stand)

138 100 968 45mm x 500mm Reflective Tape (please specify colour at time of order)

Product details

750mm x 800mm (height x length).
48mm diameter tube.
3mm wall thickness (galvanised).
2mm wall thickness (stainless).
Signage Plate: 150mm x 700mm (height x length).
Tapping Plate: 50mm x 700mm (height x length).
300mm below ground (ragged only).

Installation & use

Flanged versions require bolting onto established concrete of at least 30mm³ per leg.

Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 350mm (length x width x depth).

Allow at least 800mm between stands and a minimum of 450mm from any obstruction.

This product is guaranteed for 12 months (if installed and used correctly).



