



The AUTOPA Universal Rubber Bollard

Manufactured from recycled granulated rubber the AUTOPA Universal Rubber Bollard is extremely robust. The bollard's flexible design allows it to bend up to 45 degrees upon impact, without deforming, returning to its original position over time.

The Universal Bollard has no sharp edges and will not splinter upon impact, making it safe for pedestrians, cyclists and drivers alike. Its rubber body and flexible nature mean that expensive replacement costs are avoided should it become damaged.

Supplied ragged only, the Universal Rubber Bollard comes with a ground fixing socket for secure installations. A black finish is standard (a granite finish is also available), and reflective tape is available for added visibility.

Product Range

Order Code	Description	Weight
138 122 000	Universal (Black finish)	25.0 kg
138 122 005	Universal (Granite finish)	25.0 kg

Accessories & installation parts

138 100 968	45mm x 500mm Reflective Tape (please specify colour at time of order).
-------------	--

Product details

1000mm above ground
140mm diameter tube
780mm socket height
1780mm overall height


Installation & use

Ragged bollards require a hole of at least 780mm deep for casting into concrete and are supplied with a ground fixing socket to ensure firm ground anchorage. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103