



## The VELOPA Buckby Cycle Stand

The VELOPA Buckby Cycle Stand is a shaped tubular cycle stand. The design allows the frame of the bicycle to be secured by the users own security lock. The Buckby Cycle Stand is suitable for securing two bicycles. The Buckby Cycle Stand is available in galvanised steel, Grade 304 and Grade 316 Stainless Steel, with ragged feet for casting into new concrete or flanged feet for bolting to an existing surface.

The practical and durable nature of the VELOPA Buckby Cycle Stand stand ensures that the stand will complement any environment and offers an aesthetically pleasing alternative to the Sheffield Cycle Stand.

## Options

Order Code	Description	Weight
138 515 185	Ragged (Galvanised)	12.0kg
138 515 180	Flanged (Galvanised)	12.0kg
138 515 187	Ragged (Galvanised & Coated)	12.0kg
138 515 182	Flanged (Galvanised & Coated)	12.0kg
138 515 184	Ragged (Stainless - Grade 304)	12.0kg
138 515 184	Flanged (Stainless - Grade 304)	12.0kg
138 515 188	Ragged (Stainless - Grade 316)	12.0kg
138 515 183	Flanged (Stainless - Grade 316)	12.0kg

### Accessories & installation parts

138100994	12mm Expanding Bolt (Flanged only; 6 required per stand)
-----------	--

### Product details

750mm x 750mm (Length x Height)  
48mm outside diameter tube mild steel tube, galvanised or Grade 304/316 Stainless Steel.

## Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg.  
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth)  
Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.  
This product is guaranteed for 12 months (if installed and used correctly).



[www.velopa.co.uk](http://www.velopa.co.uk)  
+44 (0)1788 550556

AUTOPA LTD. (03428445)  
QMS 9001 (FM31071), EMS 14001 (EMS50316) & OHSAS 18001 (OHS552103).

