



## **AUTOPA Open Spaces Door Canopy**

*AUTOPA's range of door canopies are stylish, functional and can be adapted to suit every site. Manufactured in the UK, these structures can be used to provide shelter over entrances of any size.*

*Made from galvanised mild steel, all canopies can be colour coated in any BS or RAL colour as required. The roof is manufactured from a transparent, UV stable PETG glazing; this hardwearing material is designed to be vandal resistant while the transparency minimises the loss of light underneath the shelter.*

*Fully compliant with BS EN 5950, these robust structures offer a practical, attractive and versatile solution to covering outdoor spaces. Available flanged or ragged. Guttering and additional side panels are available on request.*

### **Product Range**

| <b>Order Code</b> | <b>Description</b>                                   |
|-------------------|--|
| 138 220 150       | 1500mm wide Door Canopy (Galvanised)*                |
| 138 220 250       | 2500mm wide Door Canopy (Galvanised)*                |
| 138 220 350       | 3500mm wide Door Canopy (Galvanised)*                |
| 138 220 155       | Extension Bay, 1500mm wide Door Canopy (Galvanised)* |
| 138 220 255       | Extension Bay, 2500mm wide Door Canopy (Galvanised)* |
| 138 220 355       | Extension Bay, 3500mm wide Door Canopy (Galvanised)* |

*\* Also available colour coated (BS/RAL numbers must be specified at time of order)*

### **Product details**

- Overall height: 2598mm
- Overall Depth: 1060mm
- Upright and cross beams made from 90mm x 90mm box section
- Arches made from 100mm x 60mm box section

### **Installation & use**

All door canopies are shipped in kit for installation on site. The appropriate height and lifting equipment is needed to complete the installation.

All installation work must be carried out by qualified personnel only.

Cladding and roofing needs to be drilled and fixed on site. Sheeting is clamped to the frame using clamping strips.

Flanged walkways must be bolted down onto a concrete surface (no less than 400mm<sup>3</sup>) per leg by means of 4 x 16mm anchor bolt.

Ragged versions require an excavated hole of 400mm x 400mm x 500mm per leg for setting into concrete.

This product is guaranteed for 12 months (if installed and used correctly).

[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556