



## The AUTOPA open spaces Pedestrian Guardrail

Designed to protect and guide pedestrians, the Pedestrian Guardrail from AUTOPA is ideal for busy junctions and thoroughfares. Designed in accordance with BS EN 7818 for class 1 and 2 loading, it is manufactured from highly durable mild steel and galvanised as standard to ensure its longevity.

The infill bars are made from 12mm solid mild steel bar, and the panels are available full height, or with an additional “vision gap” for areas where extra visibility is required. The panels are supplied galvanised as standard, but can be colour coated as required (BS/RAL codes must be supplied at time of order).

Available ragged only.

## Product Range

Order Code	Description	Weight
138 174 500	2 metre panel (Galvanised)	34.1kg
138 174 505	2 metre panel (Coated)	34.1kg
138 174 550	2 metre panel with Visibility Gap (Galvanised)	31.4kg
138 174 552	2 metre panel with Visibility Gap (Coated)	31.4kg

## Product details

12mm solid infill bar  
1000mm height above ground  
50mm x 30mm rectangular hollow frame  
400mm below ground

## Installation & use

Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 400mm (length x width x depth) per leg.  
This product is guaranteed for 12 months (if installed and used correctly).