







The AUTOPA Mild Steel Stepped Bollard

A functional bollard, robust in design; the Stepped Bollard is constructed using mild steel, galvanised to ensure its longevity. The step offers a decorative feature with the option of adding reflective tape for added visibility.

The bollards are available in a galvanised and a galvanised and coated finish. BS/RAL numbers must be specified at time of order.

Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured using a padlock attached to a ground socket. Please ask for more information.

Product Range			
Order Code	Description	Lift out Weight	Weight
138 121 960	139mm (removable, galvanised)*	20.4kg	25.1kg
138 121 931	152mm (removabe, galvanised)*	25.0kg	36.3kg
138 121 985	168mm (removable, galvanised)*	27.7kg	39.0kg

Accessories and Installation Parts

138 100 906 40mm Brass Padlock with 2 keys (random key)138 100 907 40mm Brass Padlock with 2 keys (identical key)

Product details

1000mm above ground 500mm below ground

Installation & use

Removable bollards require an excavated hole of at least 400mm³ for the socket (see product details for appropriate depth). AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.

This product is guaranteed for 12 months (if installed and used correctly).



