



The AUTOPA RetractaPost-GL 500

The RetractaPost-GL offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically. When raised the post is 500mm above ground, when lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.

The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is 90mm version of the RetractaPost-GL 500.

Product Range

Order Code	Description	Lift-up Weight	Weight
138 130 392	60mm (Galvanised)	3.5kg	14.4kg
138 130 397	60mm (Galvanised and Colour)	3.5kg	14.4kg
138 130 390	76mm (Galvanised)	4.2kg	15.1kg
138 130 395	76mm (Galvanised and Colour)	4.2kg	15.1kg
138 130 425	90mm (Galvanised)	5.0kg	23.5kg

Accessories & installation parts

138 811 290 Spare key (please specify key number/product)

Product details

500mm Tall (When raised).
815mm Below Ground.
Mild Steel Galvanised Socket.


Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts. An excavated hole of approximately 900mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete. The lid of the post should be no more than 10mm above finished ground level. Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103