



The AUTOPA Domed Top Bollard

The AUTOPA Domed Top Bollard combines mild steel tube with a high grade, impact resistant, malleable cast iron cap. The Domed Top Bollard is an elegantly simple bollard, ideal for providing protection against unauthorised parking or access. The Domed Top Bollard is ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The Domed Top Bollard is available in galvanised and galvanised & coated finishes. It is also available Ragged for casting in to concrete, Flanged for bolting down or in Removable versions.

The AUTOPA Domed Top Bollard is shown in 76mm galvanised tube with Ragged fixing.

Product Range

Order Code	Description	Weight
138 121 130	60mm (Ragged)	6.1kg
138 121 132	60mm (Flanged)	4.7kg
138 121 260	76mm (Ragged)	9.0kg
138 121 262	76mm (Flanged)	9.0kg
138 121 270	90mm (Ragged)	10.0kg
138 121 268	90mm (Flanged)	10.0kg
138 121 340	101mm (Ragged)	10.5kg
138 121 341	101mm (Flanged)	10.5kg
138 121 420	114mm (Ragged)	11.0kg
138 121 418	114mm (Flanged)	11.0kg

Product details

1,000mm Tall.
Ragged Posts 400mm below ground.
Galvanised steel finish.

Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm cube) by means of three M12 bolts.

Ragged bollards require a hole of at least 500mm deep for casting into concrete.

Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.

This product is guaranteed for 12 months (*if installed and used correctly*).