



GFC 6000 Removable Ornamental Bollard



The AUTOPA GFC 6000 Removable Ornamental Bollard

A substantial bollard with a clean appearance, the GFC 6000 Removable Ornamental Bollard is constructed from mild steel and galvanised to ensure its longevity. Caps and rings of cast iron are welded on to the steel body to complete the design.

The bollards are available in a galvanised and a galvanised and coated finish. RAL/BS numbers must be specified at time of order. Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured to a ground socket by means of a padlock (available separately).

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Lift out weight	Weight
138 120 097	Removable (Galvanised)	35.6kg	46.8kg
138 120 098	Removable (Galvanised and Black)	35.6kg	46.8kg
138 120 099	Removable (Galvanised and Colour)	35.6kg	46.8kg

Accessories & Installation Parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 500 065	Additional Socket

Product details

1000mm above ground
400mm below ground
168mm diameter tube
5mm wall thickness


Installation & use

Removable bollards require an excavated hole of at least 300mm square and 500mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103