



## The AUTOPA GFC 6R Removable Ornamental Bollard

A substantial bollard with a clean appearance, the GFC 6R Ornamental Bollard is constructed from mild steel and galvanised to ensure its longevity. Caps and rings of cast iron are welded on to the steel body to complete the design.

The bollards are available in a galvanised and a galvanised and coated finish. RAL/BS numbers must be specified at time of order. Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured to a ground socket by means of a padlock (available separately).

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

### Product Range

Order Code	Description	Lift out weight	Weight
138 120 177	Removable (Galvanised)	34.0kg	46.8kg
138 120 178	Removable (Galvanised and Black)	34.0kg	46.8kg
138 120 179	Removable (Galvanised and Colour)	34.0kg	46.8kg

### Accessories and installation parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 500 065	Additional Socket

### Product details

1000mm above ground  
400mm below ground  
168mm diameter tube  
5mm wall thickness


### Installation & use

Removable bollards require an excavated hole of at least 300mm square and 500mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103