

## **Stepped Bollard** 114mm

## **Galvanised or Galvanised & Colour**






A functional bollard, robust in design; the Stepped Bollard is constructed using mild steel, galvanised to ensure its longevity.

The step offers a decorative feature with the option of adding reflective tape for added visibility.

The bollards are available in a galvanised and a galvanised and coated finish. BS/RAL numbers must be specified at time of order.

Supplied Concrete in as standard, Bolt down and Removable versions are also available. Please ask for more information. Fixing down bolts for the flanged version, and padlock to secure the removable version are available at an extra cost.



| Part Number  | <u>Description</u>                | <u>Lift Weight (kg)</u> | Weight (kg) |
|--------------|-----------------------------------|-------------------------|-------------|
| 138 121 945  | Galvanised - Concrete In          |                         | 12kg        |
| 138 121 945B | Galvanised & Black - Concrete In  |                         | 12kg        |
| 138 121 945C | Galvanised & Colour - Concrete In |                         | 12kg        |
| 138 121 947  | Galvanised - Bolt Down            |                         | 12kg        |
| 138 121 947B | Galvanised & Black - Bolt Down    |                         | 12kg        |
| 138 121 947C | Galvanised & Colour - Bolt Down   |                         | 12kg        |
| 138 121 950  | Galvanised - Removable            | 12kg                    | 20kg        |
| 138 121 950B | Galvanised & Black - Removable    | 12kg                    | 20kg        |
| 138 121 950C | Galvanised & Colour - Removable   | 12kg                    | 20kg        |

## **Product details**

- 1000mm height above ground
- 114mm diameter
- Socket 300mm (below ground)

- Concrete in 400mm (below ground)
- Stepped to 101mm diameter tube

## Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556



