


Hooped Perimeter Barrier with Horizontal Rail 60mm Diameter Galvanised, Concrete In






Perimeter Barriers are designed to help secure site perimeters and provide a permanent obstacle to vehicle access, to mark boundaries, define trolley parks and protect vulnerable door entrances and exits.

Suited to sites where aesthetics and security are equally important, perimeter barriers are commonly found outside car showrooms acting as protection for the cars on the forecourt without impeding a customer's view of the vehicles.

Available in a variety of heights and widths, available as concrete in, bolt down or removable for occasional access.

Available as galvanised as standard. Stainless steel, galvanised and colour coated available extra.



Part Number	Description, Height above ground x overall width	Weight (kg)
138 176 038H	500 x 750 with Horizontal Rail, Galvanised - Concrete In	11kg
138 176 044H	500 x 1000 with Horizontal Rail, Galvanised - Concrete In	13kg
138 176 050H	500 x 1500 with Horizontal Rail, Galvanised - Concrete In	17kg
138 176 056H	500 x 2000 with Horizontal Rail, Galvanised - Concrete In	22kg
138 176 064H	750 x 1000 with Horizontal Rail, Galvanised - Concrete In	15kg
138 176 070H	750 x 1500 with Horizontal Rail, Galvanised - Concrete In	22kg
138 176 076H	750 x 2000 with Horizontal Rail, Galvanised - Concrete In	24kg
138 176 084H	1000 x 1000 with Horizontal Rail, Galvanised - Concrete In	18kg
138 176 090H	1000 x 1500 with Horizontal Rail, Galvanised - Concrete In	22kg
138 176 096H	1000 x 2000 with Horizontal Rail, Galvanised - Concrete In	26kg

Product details

- · 3mm wall thickness
- Concrete in 300mm (below ground)
- · Colour coated options available extra

Complete with horizontal rail

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

