


Hooped Perimeter Barrier with Horizontal Rail 76mm Diameter Galvanised, Concrete In





Perimeter Barriers are designed to help secure site perimeters and provide a permanent obstacle to vehicle access, to mark boundaries, define trolley parks and protect vulnerable door entrances and exits.

Suited to sites where aesthetics and security are equally important, perimeter barriers are commonly found outside car showrooms acting as protection for the cars on the forecourt without impeding a customer's view of the vehicles.

Available in a variety of heights and widths, available as concrete in, bolt down or removable for occasional access.

Available as galvanised as standard. Stainless steel, galvanised and colour coated available extra.



Part Number	Description, Height above ground x overall width	Weight (kg)
138 177 666H	500 x 750 with Horizontal Rail, Galvanised - Concrete In	14kg
138 177 680H	500 x 1000 with Horizontal Rail, Galvanised - Concrete In	17kg
138 177 684H	500 x 1500 with Horizontal Rail, Galvanised - Concrete In	22kg
138 177 688H	500 x 2000 with Horizontal Rail, Galvanised - Concrete In	27kg
138 177 664H	750 x 1000 with Horizontal Rail, Galvanised - Concrete In	19kg
138 177 670H	750 x 1500 with Horizontal Rail, Galvanised - Concrete In	25kg
138 177 676H	750 x 2000 with Horizontal Rail, Galvanised - Concrete In	30kg
138 177 659	1000 x 1000 with Horizontal Rail, Galvanised - Concrete In	22kg
138 177 656H	1000 x 1500 with Horizontal Rail, Galvanised - Concrete In	28kg
138 177 654	1000 x 2000 with Horizontal Rail, Galvanised - Concrete In	33kg

Product details

- · 3mm wall thickness
- Concrete in 300mm (below ground)
- Colour coated options available extra

Complete with horizontal rail

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

