


Hooped Perimeter Barrier with Horizontal Rail 90mm Diameter Galvanised, Concrete In





Perimeter Barriers are designed to help secure site perimeters and provide a permanent obstacle to vehicle access, to mark boundaries, define trolley parks and protect vulnerable door entrances and exits.

Suited to sites where aesthetics and security are equally important, perimeter barriers are commonly found outside car showrooms acting as protection for the cars on the forecourt without impeding a customer's view of the vehicles.

Available in a variety of heights and widths, available as concrete in, bolt down or removable for occasional access.

Available as galvanised as standard. Stainless steel, galvanised and colour coated available extra.



Part Number	Description, Height above ground x overall width	Weight (kg)
138 178 950H	500 x 750 with Horizontal Rail, Galvanised - Concrete In	17kg
138 178 951H	500 x 1000 with Horizontal Rail, Galvanised - Concrete In	20kg
138 178 956H	500 x 1500 with Horizontal Rail, Galvanised - Concrete In	26kg
138 178 962H	500 x 2000 with Horizontal Rail, Galvanised - Concrete In	32kg
138 178 966H	750 x 1000 with Horizontal Rail, Galvanised - Concrete In	23kg
138 178 972H	750 x 1500 with Horizontal Rail, Galvanised - Concrete In	29kg
138 178 978H	750 x 2000 with Horizontal Rail, Galvanised - Concrete In	36kg
138 178 982	1000 x 1000 with Horizontal Rail, Galvanised - Concrete In	26kg
138 178 988	1000 x 1500 with Horizontal Rail, Galvanised - Concrete In	33kg
138 178 994	1000 x 2000 with Horizontal Rail, Galvanised - Concrete In	39kg

Product details

- · 3mm wall thickness
- Concrete in 300mm (below ground)
- Colour coated options available extra

Complete with horizontal rail

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

