


Square RetractaPost-GL 745 745mm **Galvanised or Galvanised & Colour**








The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Tested and approved by Sold Secure.

This product has achieved Secure by Design status.

The Square RetractaPost-GL 745 offers a high premises and vehicles. The RetractaPost-GL is 745mm above ground when raised and is fabri then galvanised. When lowered the post is fully lid. The post is lockable in the raised position b high-security push button 7-pin security lock. T	s raised and lowered vertically. The post is cated from square mild steel tube which is a below ground and covered using the integral y rotating the post 45° and then pressing the



Part Number	<u>Description</u>	<u>Lift Weight (kg)</u>	Weight (kg)
138 130 381	60mm x 60mm Galvanised	5kg	18kg
138 130 386B	60mm x 60mm Galvanised & Black	5kg	18kg
138 130 386Y	60mm x 60mm Galvanised & Yellow	5kg	18kg
138 130 386	60mm x 60mm Galvanised & Colour	5kg	18kg
138 130 427	70mm x 70mm Galvanised	7kg	21kg
138 130 427B	70mm x 70mm Galvanised & Black	7kg	21kg
138 130 427Y	70mm x 70mm Galvanised & Yellow	7kg	21kg
138 130 427C	70mm x 70mm Galvanised & Colour	7kg	21kg
138 130 421	90mm x 90mm Galvanised	9kg	28kg
138 130 423B	90mm x 90mm Galvanised & Black	9kg	28kg
138 130 421Y	90mm x 90mm Galvanised & Yellow	9kg	28kg
138 130 423	90mm x 90mm Galvanised & Colour	9kg	28kg
	Cooured by Design		





Product details

- 745mm (above ground when raised)
- Socket 1070mm (below ground)
- 3mm wall thickness

- Red/white chevron tape available extra
- Other colours available on request

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556



