

## Plain Round Bollard 1500mm Above Ground 114mm - 219mm Diameter Galvanised & Yellow - Concrete In



Part Number	<u>Diameter</u>	<u>Weight (kg)</u>
138 121 448Y	114mm Galvanised & Yellow	16kg
138 121 619Y	139mm Galvanised & Yellow	33kg
138 121 679Y	152mm Galvanised & Yellow	22kg
138 121 714Y	168mm Galvanised & Yellow	40kg
138 121 808Y	193mm Galvanised & Yellow	47kg
138 121 908Y	219mm Galvanised & Yellow	53kg

## **Product details**

- 3mm wall thickness 114mm and 152mm
- 5mm wall thickness 139mm, and 168mm 219mm
- Concrete in 500mm (below ground)

## Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



## www.autopa.co.uk &44 (0)1788 550556

ISO 9001 Oualdy Nanagement Systems CERTIFIED

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP