


Wilson Shelter - Galvanised Galvanised Steel Frame Open Sided





The Wilson shelter is a free-standing, open fronted shelter designed for on site assembly, constructed from galvanised mild steel. Complete with galvanised sheet roof, and side panels. Side-to side curved roof.

Suitable as a waiting or trolley shelter. Width of 4m, with lengths from 1m-5m, extension bays can be added to achieve the desired shelter length.

Bolt down as standard.

Part Number	Description	<u>Weight (kg)</u>
138 204 630	Wilson Shelter 1m	425kg
138 204 632	Wilson Shelter 2m	529kg
138 204 634	Wilson Shelter 3m	632kg
138 204 636	Wilson Shelter 4m	736kg
138 204 638	Wilson Shelter 5m	842kg
138 204 631	Wilson Shelter 1m extension bay	
138 204 633	Wilson Shelter 2m extension bay	
138 204 635	Wilson Shelter 3m extension bay	
138 204 637	Wilson Shelter 4m extension bay	
138 204 639	Wilson Shelter 5m extension bay	

Product details

- Height 2090mm clearance, 2695mm overall
- Width 4062mm overall
- Length 1m, 2m, 3m, 4m, 5m and extensions

- Square flange plate 140mm x 140mm x 10mm
- Each flange plate requires 4 bolts
- 4mm UV stabilised PETG clear sheet panels

Installation & use

This product is guaranteed for 12 months (if installed and used correctly) Each shelter leg requires bolting down to a suitable concrete surface, using expanding anchor bolts The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes On-site assembly requires construction skill



www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP









4 x 1 138 204 630



4 x 2 138 204 632



4 x 3 138 204 634



4 x 4 138 204 636



4 x 5 138 204 638



www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

