



## Bedford Shelter Galvanised Steel Frame Open Sided







The Bedford shelter is a free-standing, open sided shelter designed for on site assembly, constructed from galvanised mild steel. Complete with a 4mm UV stabilised PETG clear sheet flat angled roof.

Suitable as a cycle shelter or walkway. Width of 2m, with lengths from 1m-5m, extension bays can be added to achieve the desired shelter length.

Bolt down as standard.



Part Number	<u>Description</u>	Weight (kg)
138 204 640	Bedford Shelter 1m	157kg
138 204 641	Bedford Shelter 2m	195kg
138 204 642	Bedford Shelter 3m	232kg
138 204 643	Bedford Shelter 4m	270kg
138 204 644	Bedford Shelter 5m	308kg
138 204 645	Bedford Shelter 1m extension bay	
138 204 646	Bedford Shelter 2m extension bay	
138 204 647	Bedford Shelter 3m extension bay	
138 204 648	Bedford Shelter 4m extension bay	
138 204 649	Bedford Shelter 5m extension bay	

## **Product details**

- Height 2168mm clearance, 2527mm overall
- Width 2159mm overall
- Length 1m, 2m, 3m, 4m, 5m and extensions

- Square flange plate 200mm x 200mm x 8mm
- · Each flange plate requires 4 bolts
- 4mm UV stabilised PETG clear sheet panels

## Installation & use

This product is guaranteed for 12 months (if installed and used correctly)

Each shelter leg requires bolting down to a suitable concrete surface, using expanding anchor bolts

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes

On-site assembly requires construction skill



www.autopa.co.uk +44 (0)1788 550556





## Bedford Shelter Galvanised Steel Frame Open Sided













www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

