







# The AUTOPA Square RetractaPost-GL 500

The Square RetractaPost-GL 500 offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically. The post is 500mm above ground when raised and is fabricated from square mild steel tube which is then galvanised.

When lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.

The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is the 60mm Square RetractaPost-GL galvanised with optional AUTOPA Red & White chevron reflective label.

### **Product Range**

Order Code	Description	Lift-up Weight	Weight
138 130 391	60mm x 60mm (Galvanised)	4.2kg	15.1kg
138 130 396	60mm x 60mm (Galvanised and Colour)	4.2kg	15.1kg

## **Accessories & installation parts**

138 811 290 Spare key (please specify key number/product)

138 810 598 AUTOPA Red & White Chevron Reflective Label

### **Product details**

500mm Tall (When raised). 815mm Below Ground. Galvanised or galvanised and coated finish.

# Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.

An excavated hole of approximately 900mm deep and 300mm diameter is required for installation.

Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete.

The lid of the post should be no more than 10mm above finished ground level.

Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar.

This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

