







## The AUTOPA RemovaPost-GL

The RemovaPost-GL offers a highly effective and robust way to protect premises and vehicles. The RemovaPost-GL is supplied with a shallow fitting ground socket from which the post can be removed and placed to one side when not in use. This solution is ideal where the ground prevents the use of Retractable posts. The post is lockable by placing the post in the socket, rotating the post 45° and then pressing the high-security push button 7-pin lock. The post is unlocked, using the supplied key, rotated and then removed.

The RemovaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

The AUTOPA RemovaPost-GL is shown in galvanised finish with optional AUTOPA Red & White chevron reflective label.

## **Product Range**

Order Code	Description	Lift-out Weight	Weight
138 100 751	Galvanised	10.0kg	19.0kg
138 100 759	Stainless Grade 304	10.0kg	19.0kg

## **Accessories & installation parts**

138 501 420 Additional Ground Socket
 138 811 290 Spare key (please specify key number/product)
 138 810 598 AUTOPA Red & White Chevron Reflective Label

## **Product details**

745mm above ground.313mm socket depth.90mm outside diameter galvanised steel tube body.

# Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.

The ground socket must be concreted into a hole of approximately 350mm cubed.

The flap should be flush with the surrounding ground level when closed.

Suitable provision for should be allowed for drainage from the bottom of the excavated hole.

This product is guaranteed for 12 months (if installed and used correctly).



