



The AUTOPA Swing Gate

The AUTOPA Swing Gate is a manually operated gate designed for securing commercial and industrial site entrances where only occasional access control is required.

Robust and reliable, several safety features are incorporated into the design of the Swing Gate as standard, including a self-latching catch post, short leading edge beam and low bottom edge. All these combined reduce the chances of the gate swinging open unexpectedly while also decreasing the risk of injury should it do so. The gate can be locked in both the closed and open positions (a second catch post is required) using a padlock (available separately).

Manufactured from galvanised mild steel, the gate is colour coated red as standard (other colours are available upon request; please state BS/RAL numbers at time of order) and is available ragged or flanged.

Options

Order Code	Description	Weight
138 106 430	3m (Flanged) Galvanised and Colour	81.0kg
138 106 440	4m (Flanged) Galvanised and Colour	95.3kg
138 106 450	5m (Flanged) Galvanised and Colour	106.3kg
138 106 460	6m (Flanged) Galvanised and Colour	117.3kg
138 106 470	7m (Flanged) Galvanised and Colour	128.3kg

Accessories & installation parts

138 106 480	Catch Post (Flanged)	35.2kg
138 100 991	M16 Expanding Bolt (4 required per gate)	
138 100 994	M12 Expanding Bolt (4 required per catch post)	
138 100 906	40mm Brass Padlock with 2 Keys	

Product details

Main Body: 120mm x 120mm square tube
 Main Gate Arm: 60mm x 60mm square tube
 Catch Post Body: 90mm x 50mm tube
 3mm wall thickness
 600mm below ground (ragged gate only)
 400mm below ground (ragged catch post only)

Installation & use

Flanged Swing Gates require bolting down to a suitable concrete surface by means of four 16mm bolts.
 Flanged Catch Posts require bolting down to a suitable concrete surface by means of four 12mm bolts.
 Ragged Swing Gates require an excavated hole of at least 600mm³ for casting into concrete.
 Ragged Catch Posts require an excavated hole of at least 400mm³ for casting into concrete.
 This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
 +44 (0)1788 550556

AUTOPA Limited
 Cottage Leap, Rugby, Warwickshire CV21 3XP

