



The VELOPA Fin Cycle Stand

The VELOPA Fin Cycle Stand offers site owners a secure and stylish cycle stand that complements every architectural style. The hooped design allows cyclists to secure both the frame and wheel of their bicycle to the stand using their own security lock and is suitable for securing two bicycles.

Manufactured from galvanised mild steel as standard, the Fin is also available in galvanised and coated and stainless steel finishes; BS or RAL colour codes must be specified at time of order. The Fin Cycle Stand can be supplied ragged for casting into new concrete or flanged for bolting onto existing concrete.

Options

Order Code	Description	Weight
138 515 190	Flanged (Galvanised)	7.8kg
138 515 191	Flanged (Galvanised & Coated Black)	7.8kg
138 515 192	Flanged (Galvanised & Coated; Please specify BS/RAL)	7.8kg
138 515 194	Flanged (Stainless Steel)	6.6kg
138 515 195	Ragged (Galvanised)	9.0kg
138 515 196	Ragged (Galvanised & Coated Black)	9.0kg
138 515 197	Ragged (Galvanised & Coated; Please specify BS/RAL)	9.0kg
138 515 199	Ragged (Stainless Steel)	7.8kg

Accessories & installation parts

138 100 994	12mm Expanding Bolt (Flanged only; 6 required per stand)
-------------	--

Product details

- 750mm x 1020mm (Height x Length)
- 48mm diameter tube
- 3mm wall thickness (Galvanised)
- 2.5mm wall thickness (Stainless Steel)
- 300mm below ground (ragged only)

Installation & use

Flanged versions require bolting to established concrete of at least 300mm³ per leg.
 Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth) per leg.
 Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.
 This product is guaranteed for 12 months (if installed and used correctly).

www.autopa.co.uk
 +44 (0)1788 550556

AUTOPA Limited
 Cottage Leap, Rugby, Warwickshire CV21 3XP

