



## The VELOPA Kirby Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles. The Kirby is a rolled variant of the ever popular Sheffield cycle stand.

The practical and durable nature of the VELOPA Kirby cycle stand ensures it has been consistently recommended by cycling groups since it's introduction in the 2000's.

Shown is the galvanised flanged version of the Kirby Cycle Stand.

### Options

Order Code	Description	Weight
138515145	Ragged (Galvanised)	10.0kg
138515140	Flanged (Galvanised)	10.0kg
138515147	Ragged (Galvanised & Coated; specify BS/RAL colour)	10.0kg
138515142	Flanged (Galvanised & Coated; specify BS/RAL colour)	10.0kg
138515155	Ragged (Stainless)	10.0kg
138515150	Flanged (Stainless)	10.0kg

### Accessories & installation parts

138100994	M12 Expanding Bolt (Flanged only; 6 required per stand)
138100993	M12 Foundation Bolt (Flanged only; 6 required per stand)
138100995	M12 Anchor Bolt (Flanged only; 6 required per stand)

### Product details

750mm x 750mm (Length x Height)  
48mm outside diameter tube.

### Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg.  
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth) per leg.  
Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.  
This product is guaranteed for 12 months (if installed and used correctly).



[www.velopa.co.uk](http://www.velopa.co.uk)  
+44 (0)1788 550556

AUTOPA LTD. (03428445)  
QMS 9001 (FM31071), EMS 14001 (EMS50316) & OHSAS 18001 (OHS552103).

