



The VELOPA EcoSheffield Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles. The EcoSheffield is a reduced footprint variant of the ever popular Sheffield cycle stand.

The practical and durable nature of the VELOPA EcoSheffield cycle stand ensures it has been consistently recommended by cycling groups since it's introduction in the 2000's.

Shown is the galvanised flanged version of the EcoSheffield Cycle Stand.

Options

Order Code	Description	Weight
138 515 165	Ragged (Galvanised)	9.0kg
138 515 160	Flanged (Galvanised)	9.0kg
138 515 167	Ragged (Galvanised & Coated; specify BS/RAL colour)	9.0kg
138 515 162	Flanged (Galvanised & Coated; specify BS/RAL colour)	9.0kg
138 515 175	Ragged (Stainless)	9.0kg
138 515 170	Flanged (Stainless)	9.0kg

Accessories & installation parts

138 100 994	M12 Expanding Bolt (Flanged only; 6 required per stand)
138 100 993	M12 Foundation Bolt (Flanged only; 6 required per stand)
138 100 995	M12 Anchor Bolt (Flanged only; 6 required per stand)

Product details

340mm x 750mm (Length x Height)
48mm outside diameter tube.

Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg. Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth) per leg. Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction. This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103