



The VELOPA Motorcycle Security Barrier

The Motorcycle Security Barrier is ideal for securing motorcycles. The Security Barrier is based upon a standard perimeter barrier of 76mm outside diameter tube, but has the addition of loose steel bars inserted into the lower horizontal tube and legs, this greatly increases the difficulty of cutting through the tube in order to make away with anything locked to the barrier. The Motorcycle Security Barrier is fully galvanised and only available in a Ragged finish for casting into the ground.

The sign shown is available at extra cost.

Options

Order Code	Description	Weight
138 200 124	Motorcycle Security Barrier (2,000mm x 1,000mm)	40.0kg

Product details

1,300mm x 2,000mm (Height; overall x Length)
300mm below ground.
Galvanised Mild Steel.
Steel bar inserted in lower horizontal tube and legs.

Installation & use

Installation requires setting with concrete into a hole of at least 300mm x 300mm x 350mm (length x width x depth)
Allow 800-1,000mm between loops and a minimum of 450mm from any obstruction.
This product is guaranteed for 12 months (if installed and used correctly).



www.velopa.co.uk
+44 (0)1788 550556

AUTOPA LTD. (03428445)
QMS 9001 (FM31071), EMS 14001 (EMS50316) & OHSAS 18001 (OHS552103).

