



## The AUTOPA Wheel Guide

The AUTOPA Wheel Guide is ideal for providing guidance for reversing vehicles in loading bays. The Wheel Guide is available in 76mm or 90mm outside diameter mild steel galvanised tube which can be coated yellow to increase visibility. The Wheel Guide is available in two lengths, 1,500mm or 2,000mm.

All products in the range are galvanised mild steel, ensuring their longevity and are designed to take the knocks and bumps that occur in the warehouse and factory environment. The Wheel Guide is also suitable for us as a low level protection rail.

The 76mm o.d. x 1,500mm coated yellow version is shown.

## Product Range

Order Code	Description	Weight
138 177 920	76mm x 1,500mm (Galvanised)	12.0kg
138 177 921	76mm x 1,500mm (Galvanised and Yellow)	12.0kg
138 177 925	76mm x 2,000mm (Galvanised)	15.0kg
138 177 926	76mm x 2,000mm (Galvanised and Yellow)	15.0kg
138 177 930	90mm x 1,500mm (Galvanised)	13.5kg
138 177 931	90mm x 1,500mm (Galvanised Yellow)	13.5kg
138 177 935	90mm x 2,000mm (Galvanised)	16.7kg
138 177 936	90mm x 2,000mm (Galvanised Yellow)	16.7kg

## Accessories & installation parts

138 100 994 M12 Expanding Bolt (8 required per Wheel Guide)

## Product details

320mm tall. Width size measurement to outside edge of flange.  
Flanged for bolting to a suitable surface.  
Galvanised steel finish.


## Installation & use

Wheel Guides require bolting down to a suitable concrete surface (no less than 300mm cube) by means of four M12 bolts for each flange.  
This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103