



GFC 2R Ornamental Bollard

The GFC 2R Ornamental Mild Steel Bollard from AUTOPA is suitable for a wide range of locations and purposes. The main post is constructed using mild steel, galvanised to ensure its longevity. Two cast iron rings are welded onto the steel tube to complete the design.

The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Lift out weight	Weight
138 120 157	Removable (Galvanised)	13.1kg	17.8kg
138 120 158	Removable (Galvanised and Black)	13.1kg	17.8kg
138 120 159	Removable (Galvanised and Colour)	13.1kg	17.8kg

Accessories and installation parts

138 100 990	40mm Brass Padlock with 2 keys (Random Key)
138 100 992	40mm Brass Padlock with 2 keys (Identical Key)
138 150 206	Additional Socket

Product details

1000mm above ground
267mm below ground
114mm diameter tube
3mm wall thickness

Installation & use

Removable bollards require an excavated hole of at least 300mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).