



The AUTOPA GFC 3000 Ornamental Bollard

With a practical and classic appearance the GFC 3000 Ornamental Mild Steel Bollard is suitable for various locations and purposes.

The main post is constructed from mild steel, galvanised to ensure its longevity. Caps and rings of cast iron are welded on to the steel body to complete the design.

The bollards are available in a galvanised and a galvanised and coated finish. RAL numbers must be specified at time of order. Supplied ragged as standard, flanged and removable options are available. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

| Order Code | Description | Weight |
|---|---|--------|
| 138 120 061 | Ragged (Galvanised) | 13.5kg |
| 138 120 062 | Ragged (Galvanised and Black) | 13.5kg |
| 138 120 063 | Ragged (Galvanised and Colour) | 13.5kg |
| 138 120 064 | Flanged (Galvanised) | 11.0kg |
| 138 120 065 | Flanged (Galvanised and Black) | 11.0kg |
| 138 120 066 | Flanged (Galvanised and Colour) | 11.0kg |
| Accessories and installation parts | | |
| 138 100 994 | M12 Expanding Bolt (3 required per bollard) | |

Product details

900mm above ground
300mm below ground
114mm diameter tube
3mm wall thickness


Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm³) by means of three M12 bolts. Ragged bollards require a hole of at least 500mm deep for casting into concrete & are supplied with welded fixing spikes to ensure firm ground anchorage. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103