



**The AUTOPA GFC 9000 Ornamental Bollard**

A substantial bollard, with a simple, clean appearance. The GFC 9000 Ornamental Bollard is constructed using mild steel, galvanised to ensure its longevity. A decorative welded steel cap is added to complete the design.

This bollard is designed to work in combination with the GFC 9000i Illuminated Bollard, where an illuminated version is not required. The bollards are available in a galvanised and a galvanised and coated finish. BS/RAL numbers must be specified at time of order.

Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured to a ground socket by means of a padlock. Please ask for more information.

**Product Range**

Order Code	Description	Lift Out Weight	Weight
138 122 601	Ragged (Galvanised)		24.0kg
138 122 602	Flanged (Galvanised)		20.9kg
138 122 607	Removable (Galvanised)	22.9kg	27.6kg

**Accessories and Installation Parts**

138 100 906	40mm Brass Padlock with 2 keys (random key)
138 100 907	40mm Brass Padlock with 2 keys (identical key)
138 100 994	M12 Expanding Bolt (3 required per bollard)

**Product details**

- 1000mm above ground
- 400mm below ground (ragged only)
- 500mm below ground (removable)
- 139mm diameter tube
- 5mm wall thickness

**Installation & use**

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm<sup>3</sup>) by means of three M12 bolts.  
 Removable bollards require an excavated hole of at least 300mm square and 500mm deep for the socket.  
 Ragged bollards require a hole of at least 500mm deep for casting into concrete.  
 AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.  
 This product is guaranteed for 12 months (if installed and used correctly).



[www.autopa.co.uk](http://www.autopa.co.uk)  
 +44 (0)1788 550556

AUTOPA Limited  
 Cottage Leap, Rugby, Warwickshire CV21 3XP

