

Sheffield Cycle Stand Galvanised or Galvanised & Colour








The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles.

The practical and durable nature of the VELOPA Sheffield cycle stand ensures it has been consistently recommended by cycling groups since its introduction in the 1990's.



Part Number	Description	<u>Weight (kg)</u>
138 200 111	Galvanised, Concrete in	9.7kg
138 200 105	Galvanised & Colour, Concrete in	9.7kg
138 200 112	Galvanised & Black, Concrete in	9.7kg
138 200 101	Galvanised, Bolt down	8.2kg
138 200 104	Galvanised & Colour, Bolt down	8.2kg
138 200 102	Galvanised & Black, Bolt down	8.2kg
138 100 994	M12 Expanding Bolt (6 required per stand)	

Product details

48mm diameter

Ragged version 300mm below ground

Installation & use

Bolt down cycle stand require bolting to established concrete (no less than 300mm³) by means of six M12 bolts per stand. Concrete in cycle stands require an excavated hole (no less than 300mm3) for installation. Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction. This product is guaranteed for 12 months (if installed and used correctly).





bsi, 9001 Quality Management
ISO 14001 Environmental Management
OHSAS 18001 Occupational Management

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

FM 31071 EMS 503166 OHS 55210